



IP camera with GenSTAR IVS 2.0 analytics



Model	ZN8-81DT4M213NL
Sensor	1/2.8" CMOS
Sensitivity (AGC ON)	Color: 0.03lux @ F1.2 / IR ON: 0lux
Day/Night Mode	IR-Cut automatic filter
Electronic Shutter.	1/5 - 1/20.000
Aperture	Auto-Iris
WDR mode	d-WDR
Noise reduction	2D / 3D-DNR
Lens	Motor-zoom with AF: 2.7 - 13.5mm (96° ~ 30°)
IR illuminator	4 x IR LED, range up to 30 meters
AV compression	H.265 H.264 MJPEG G.711U G.711A RAW
Bitrate (CBR/VBR)	Stream 1: 512 Kbps - 6 Mbit
	Stream 2 and 3: 128 Kbps - 3 Mbit
Resolution and cages	2560x1440 and 2304x1296 (25fps).
	1920x1080 and 1280x720 (25fps).
Video streams	Stream 1: 2560x1440 (4MP) max.
	Stream 2: 720x576 (D1) max.
	Stream 3: 640x480 (VGA) max.
Image settings	Rotation, saturation, brightness, contrast, sharpness
Digital functions	HLC BLC ROI DEFOG
Corridor mode	Yes (9:16)
Privacy masks	4 zones
Events	Motion detection (22x18 grid),
	GenSTAR IVS 2.0 analytics , D/N switching,
Network protocols	TCP, UDP, IPv4/6, HTTP/S, DHCP, FTP, SMTP,
	DNS, DDNS, NTP, RTP, RTSP, RTCP, Multicast
	Unicast, uPNP, WS-Discovery, SSL, PPPoE
RTSP support	RFC2326 standard (VLC Player / QuickTime).
Security	User authentication, hardware WatchDog
Compatibility	ONVIF, HTTP API
Ethernet interface	10/100 Base-T, RJ45
Audio	N/A
Alert	N/A
Analog output.	N/A

ZN8-81DT4M213NL



Special features:

- **GenSTAR IVS 2.0 - AI (Artificial Intelligence) analytics** - artificial intelligence using *DeepLearning* algorithms to provide instant and precise detection and recognition of objects like person, vehicle.
- **Smart Encode** - dynamically adaptable network stream and codec parameters for continuous recording while minimizing archive space requirements.
- **Scheduling of the image sensor** - the ability to configure the operation of the image sensor depending on the time or Day/Night mode.
- **Corridor mode** - adjusting the field of view to a scene characterized by a significant disparity between the height and width of the usable area.
- **NDAA-compliant** - devices that comply with a US congressional law called the National Defense Authorization Act.

Functional capabilities of AI analytics: GenSTAR IVS 2.0

AI engine features (Artificial Intelligence)	Object detection: <i>DeepLearning</i> engine
	Detection: face of a person, person, vehicle.
	Object classification: person, vehicle (Detector)
	Track multiple objects simultaneously (Tracker)
Behavioral detection	Trespassing, Swaggering,
	Intersection of single/double perimeter lines.

Technical parameters

Reset button	Yes
SD card support	Micro SD / SDHC / SDXC slot, max. 256GB
Power supply	12VDC / PoE (802.3af / class-3)
Current consumption	5W (IR-LED OFF) / 9W (IR-LED ON)
Power output	N/D
Operating temperature	-30°C ... +50°C
Max humidity	90%
Certifications and classes	CE / FCC / IP67 / IK10
Dimensions / weight	Ø 130 (base) x 112 mm / 750g
Range of adjustment	350° (H) / 80° (V) / 330° (Transmitter rotation)

© CBC | Rev.2023.06

CBC Tokyo
CBC
CBC
CBC
CBC Mishima

CBC New
CBC Los Angeles
CBC Mexico
CBC
CBC DongGuan

CBC
CBC
CBC
CBC
CBC Bangladesh

CBC
CBC
CBC
CBC UK
CBC Germany

CBC
CBC
CBC
CBC
CBC India

CBC Poland sp. z o.o.
8 Rydygiera St. bud. 17
01-793 Warsaw
kontakt@ganzsecurity.pl
www.ganzsecurity.pl

Adapters
for installation:



ZA8-JBMP-2
(C holes)



ZA8-CBK627B

ZA8-CBK627B
only in combination
with
ZA8-JBMP-2

Compatibility:



PixelMASTER



GenSTAR NVR



CORTROL VMS



NDA Directive

External dimensions:

