



IP camera with video analytics for
face/person/vehicle detection



ZN8V-71B5F28DT-J4A



Key features:

- **Smart Encode** - dynamically adapts network stream and codec parameters to maintain recording continuity while minimizing storage requirements.
- Built-in IR and warm-light illumination; smart illumination range up to 40 m.
- **Active deterrence** - supports **red and blue** alarm lights and a **speaker** to warn intruders.
- **ROI** (Region of Interest, up to 8 zones) - based on user-defined ROI zones, the camera reduces image quality outside these zones to lower bandwidth usage (bitrate), while maintaining maximum image quality within the ROI zones.
- Supports **face/person/vehicle detection**
- Supports **P2P cloud connectivity**
- **SMART-IR** - automatically adjusts IR LED intensity to prevent overexposure of objects (e.g. a person's face) near the camera.
- **True-WDR** - digital wide dynamic range function.
- **Image sensor schedules** - allow sensor operation to be configured by time or Day/Night mode.
- **NDA compliant** with the U.S. National Defense Authorization Act.
- **Built-in microphone** for audio communication.
- **Built-in speaker**

Model	ZN8V-71B5F28DT-J4A
Image sensor	1/2.7" Progressive Scan CMOS, 5MP
Sensitivity (AGC ON)	Color: 0.01 lux @ F1.6 / B/W: 0 lux with IR
Day/Night mode	Automatic IR-cut filter
Electronic shutter	Auto/Manual, 1/5 to 1/20,000 s
Iris	Fixed Iris
WDR mode	True WDR
Noise reduction	2D / 3D-DNR
Lens	2.8 mm, H: 110.9°, V: 60°
Illuminators	IR range up to 40 m, white-light range up to 30 m
AV compression	H.265 H.264 MJPEG G.711U G.711A RAW
Bitrate (CBR/VBR)	Stream 1: 200 Kbps - 12 Mbit
	Stream 2: 100 Kbps - 6 Mbit
	Stream 3: 100 Kbps - 3 Mbit
Resolution and frame rate	2880x1620, 2304x1296, 1920x1080, 1280x720 (25/30 fps)
	D1, VGA, CIF (25/30 fps)
	VGA, CIF, QVGA (25/30 fps)
Image settings	Rotation, saturation, brightness, contrast, sharpness
Digital functions	HLC / BLC / ROI / DEFOG
Privacy masks	4 zones
Motion detection	22x18 grid
IVS events	Intrusion, line crossing, double-line crossing, loitering, wrong direction, illegal parking and intelligent motion detection. Supports alarm triggering by specified target types (people and vehicles).
Network protocols	TCP, UDP, IPv4/6, HTTP/S, DHCP, FTP, SMTP, DNS, DDNS, NTP, RTP, RTSP, RTCP, Multicast
	Unicast, uPNP, WS-Discovery, SSL, PPPoE
RTSP support	Standard RFC2326 (VLC Player / QuickTime)
Security	User authorization, hardware watchdog
Compatibility	ONVIF (Profile S/T/G/M), SDK, CGI
Ethernet interface	10/100 Base-T, RJ45
Audio	1x In / 1x Out
Audio codec	G.711 (64kb/s), 128Kbps (RAW_PCM)
Alarm	1x In / 1x Out

Technical specifications	
Reset button	Yes
SD card support	MicroSD card slot, max. 1 TB
Microphone	Built-in microphone
Speaker	Built-in speaker
Power supply	12 VDC (-15% to +25%)/PoE (802.3af)
Power draw	2 W, max. 9.5 W (lights + speaker)
Max. humidity	<90%
Certifications	CE / EN / FCC / IP66
Size / weight	188.0 × 80 × 77 mm / 0.58 kg
Operating temp.	-30°C ~ +60°C
Housing	Aluminum alloy

Security	
OS / Firmware protection	Encrypted firmware, secure boot, signed firmware
User authentication	Digest authentication, brute-force attack protection
Network authentication	IEEE 802.1X (EAP-TLS)
Secure communication	HTTPS, WSS (WebSocket Secure), SRTP
Access control	IP address-based access control, automatic logout
Data protection	Credential encryption
Secure data storage	AES-256 encryption of the SD card partition and a hardware Secure Element
Audit	Access / system / event log management
Supply chain security	SBOM

Built-in GENSTAR IVS 2.0 video analytics (AI analytics)



AI multi-object



Intrusion



Intelligent detection



Line crossing



Double line



Group loitering



Wrong direction



Illegal parking



People counting

DORI Distance						
Lens		Detection	Observation	Recognition	Identification	
2.8 mm		64 m	25.6 m	12.8 m	6.4 m	
OODPCVS Distance (OODPCVS distances calculated from pixel-density thresholds per IEC/EN 62676-4:2025.)						
Overview	Object outline	Object differentiation	Behavior perception	Object characteristics	Verification	Detailed analysis
80 m	40 m	20 m	12.8 m	6.4 m	3.2 m	1.1 m

Mounting adapters:



ZA8-CBK656A



ZA8-CBK627B

Compatibility:



GENSTAR NVR



CORTROL VMS



NDAA compliance

© CBC | Rev.2026.07

CBC Tokyo HQ
CBC Osaka
CBC Nagoya
CBC Fukuoka
CBC Mishima

CBC New Jersey
CBC Los Angeles
CBC Mexico
CBC Beijing
CBC DongGuan

CBC Shanghai
CBC HongKong
CBC Singapore
CBC Taiwan
CBC Bangladesh

CBC Guangzhou
CBC Indonesia
CBC Thailand
CBC UK
CBC Germany

CBC Poland
CBC Italy
CBC Spain
CBC Russia
CBC India

CBC Poland sp. z o.o.
8 Rydygiera St., Bldg. 17
01-793 Warsaw
kontakt@ganzsecurity.pl
www.ganzsecurity.pl

External dimensions:

